

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06T 9/40, H04N 1/64		A1	(11) International Publication Number: WO 98/19273
			(43) International Publication Date: 7 May 1998 (07.05.98)
(21) International Application Number: PCT/AU97/00724			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 28 October 1997 (28.10.97)			
(30) Priority Data: PO 3293 28 October 1996 (28.10.96) AU			
(71) Applicants (for all designated States except US): COMMONWEALTH SCIENTIFIC AND INDUSTRIAL RESEARCH ORGANISATION [AU/AU]; Limestone Avenue, Campbell, ACT 2612 (AU). AUSTRALIAN NATIONAL UNIVERSITY [AU/AU]; Acton, ACT 2600 (AU).			
(72) Inventor; and (75) Inventor/Applicant (for US only): BONE, Donald, James [AU/AU]; 7 Tambo Street, Kaleen, ACT 2617 (AU).			
(74) Agent: PIZZEYS PATENT & TRADEMARK ATTORNEYS; P.O. Box 291, Woden, ACT 2606 (AU).			


Published

With international search report.

(54) Title: IMAGE TRANSMISSION

(57) Abstract

A method of progressively transmitting an image is disclosed in which image compression techniques rely on spatial tiling of the image, wherein variable priority values are allocated to spatial regions within the image whereby a receiver of a transmitted image can interactively define the spatial focus of the image during transmission thereof.



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

"IMAGE TRANSMISSION"**Technical Field**

This invention relates to a system for and method of
5 image transmission.

The invention has particular application to
progressive image transmission systems.

Background of Invention

10 Progressive image transmission systems are known and
involve the transmission of image data in a way that the
data received at the intermediate stages in the
transmission can be used to reconstruct an approximation
to the full image. In practice this is most efficiently
15 achieved with an embedded image representation wherein an
exact or nearly exact representation of the image is
organised in such a way that any truncation of the
bitstream resulting from the encoding can be used to
reconstruct an approximation to the image which minimises
20 the distortion for a given codelength.

Progressive image transmission has the advantage
that the user can quite quickly see an approximation to
the full image and can make decisions on that basis to
terminate or react in some other way to the transmission
25 at the earliest possible point.

In order to take advantage of the redundancy
associated with local pixel correlation in most images,
and for reasons of computational efficiency, image
compression techniques typically rely on some form of
30 spatial tiling. In the case of the JPEG standard this is
an explicit tiling of the image into 8x8 pixel blocks as
seen in FIG 1 which illustrates a standard JPEG image
tiling. The assumption that the underlying image
representation divides the image into spatial tiles is
35 explicit in the case of JPEG or implicit in the case of
most implementations of the discrete wavelet transform
(DWT).

It is not entirely obvious that the wavelet

transform divides the image into spatial tiles and it is only possible to view the DWT in this way because in general, it is only useful from the point of view of compression to hierarchically decompose the image on the wavelet basis to the point that the scaling function (DC) components are spatially decorrelated. For most images a depth of 3-5 levels in the hierarchy is sufficient to achieve this. The coefficients in the wavelet domain can then be collected into groups of components for which the centres of the corresponding basis function lie within a given spatial region of the image.

As can be seen in FIG 2 which illustrates a Mallet-style hierarchical wavelet decomposition with the components which constitute a spatial tile, the collection of coefficients in the wavelet domain can be thought of as a spatial tile with one DC component (at the top left of FIG 2), and an hierarchy of AC components in a scale hierarchy mimicking the structure of the image subbands. By reconstructing the components in each spatial tile it is possible to arrive at a set of orthogonal but overlapping image partitions which can be added together to reform the image.

FIG 3 illustrates a tiled wavelet coding in which the components of the standard Mallet style hierarchy are re-ordered to form spatial tiles whose arrangement follows that of the associated DC component in the standard Mallet hierarchy.

Each tile in a tiled representation of an image is represented as a stream of bits. One known manner of encoding a tile into a bit stream is that the resulting representation is embedded. An embedded coding is one in which the bits representing the image have been structured in a single stream which can be truncated at any point so that an approximation to the image can be generated from the information to that point and such that approximation has close to optimal distortion for the proportion of the information received.

Embedded encodings are well known. The simplest

embedded encoding re-orders the bit planes so that the most significant bits are sent first. Simple run length encoding is then able to achieve some compression while retaining the embedded character of the representation.

5 Such methods do not result in great compression.

More successful examples of embedded encodings are the Embedded Zerotree Wavelet (EZW) coding of Shapiro and the related Spatial Partitioning In Hierarchical Trees (SPIHT) encoding of Said and Pearlman. See the
10 following:-

A.Said, W.A.Pearlman, "A New Fast and Efficient Image Codec Based on Set Partitioning in Hierarchical Trees," Transactions on Circuits and Systems for Video Technology vol. 6(3). JUN pp 243-250 (1996);

15 J.M.Shapiro, "Embedded image coding using zerotrees of wavelet coefficients," IEEE, Trans. on SP, 41 (1993), pp 3445-3462;

J.M.Shapiro, "An Embedded Hierarchical Image Coder using Zerotrees of Wavelet Coefficients," Proc. Data
20 Compression Conference, J.Storer, M.Cohn Eds (1992), pp 214-223, and

US Patents 5412741, 5321776 and 5315670 to Shapiro.

Summary of Invention

25 The present invention aims to provide an alternative to known progressive image transmission systems and methods.

This invention in one aspect resides broadly in a method of progressively transmitting an image in which
30 image compression techniques rely on spatial tiling of the image, the method including:-

allocating variable priority values to spatial regions within the image whereby a receiver of a transmitted image can interactively define the spatial
35 focus of the image during transmission thereof.

It is preferred that variable priority values are allocated to independent spatially localised tiles within the image by encoding an embedded representation such

that truncations of the representations for each tile can be used to generate valid approximations to the tiles.

In a preferred embodiment the compression techniques are based on embedded zero tree coding systems.

5 The method may further include:-

 separating the bitstreams associated with each tile and weighting each bit.

 In a preferred embodiment the method further includes:-

10 establishing an algorithm at each end of the transmission to determine the ordering of the information from the tiles.

 Suitably the bits are weighted by assigning a priority index for each tile, the priority index
15 -comprising a first unsigned integer having a sufficient number of bits to facilitate fine increments of priority.

 It is preferred that the priority index for each tile is an integer within a predetermined range and that the method further includes:-

20 transmitting a number of bits from the tile stream which equals the priority index.

 The bits in the bitstring representation of each tile are preferably weighted in accordance with the length of each bitstring.

25 The method may also include:-

 assigning a priority accumulator to each tile, the priority accumulator comprising a second unsigned integer value;

 scanning the tiles in a preset order and at each
30 pass thereof incrementing the priority accumulator of each tile by the priority index, and

 transmitting a quantity of information each time the accumulator overflows.

 The method of the present invention is suitable for
35 implementation by appropriate software or purpose built hardware.

 Accordingly in another aspect this invention resides broadly in an image transmission system for progressively

transmitting an image in which image compression techniques rely on spatial tiling of the image, the system including:-

5 prioritising means for allocating variable priority values to spatial regions within the image whereby a receiver of a transmitted image can interactively define the spatial focus of the image during transmission thereof.

10 In a preferred embodiment the system further includes:-

separating means for separating the bitstreams associated with each tile, and

weighting means for weighting each bit.

The system may also include:-

15 means for establishing an algorithm at each end of the transmission to determine the ordering of the information from the tiles.

It is also preferred that the system includes:

20 assigning means for assigning a priority accumulator to each tile, the priority accumulator comprising a second unsigned integer value,

scanning means for scanning the tiles in a preset order and at each pass thereof incrementing the priority accumulator of each tile by the priority index, and

25 transmitting means for transmitting a quantity of information each time the accumulator overflows.

Description of Drawings

30 In order that this invention may be more easily understood and put into practical effect, reference will now be made to the accompanying drawings which illustrate a preferred embodiment of the invention, wherein:-

FIGS 1 to 3 illustrate known tiled image representation techniques as described above;

35 FIG 4 illustrates the bitstrings resulting from the embedded coding of each spatial tile, and

FIG 5 illustrates the priority variables in accordance with the present invention from a series of

scans of one tile.

Description of Preferred Embodiment of Invention

The present invention utilises a transformation
5 wherein the transformed representation of the image can
be considered to be organised as spatial tiles. Although
in the most general case the tiles could be single pixels
or single coefficients of some transformation, this does
not lead to efficient implementation and it is preferred
10 that the nature of the spatial tiling implies no
interdependence between the spatial tiles in the
decoding. The encoding of the tile into a bitstream is
also preferably done in such a way that the resulting
representation is embedded.

15 The present invention generalises the concept of
embedded encoding to some extent in that the method of
the present invention embeds the representation of each
tile in the usual sense. Thus if the priority given to
each tile were to be equal and the bitstreams from each
20 tile were to be interleaved so that bits of equal
significance appear at similar points in the stream, then
the resulting representation of the full image can be
regarded as having been embedded in the usual sense.

However as will subsequently be described, in the
25 present invention the separation of the streams
associated with each tile facilitates the incorporation of
spatial weighting into the determination of the
significance of each bit in the stream. This is referred
to as spatial prioritisation.

30 In applications where some spatial regions of the
image have priority over other spatial regions, bits from
some blocks will be less important than bits from other
blocks. The system of the present invention is
implemented without significant bitstream overheads and
35 tile index information is not transmitted. In order to
facilitate the client/receiver being able to ascertain to
which tile each incoming bit belongs, a simple algorithm
is established at each end of the transmission to

determine the ordering of the information from the tiles.

At the server end, the encoded image has the form of an array of bit strings, one associated with each spatial tile. The server scans through this array and at each
5 tile it must decide how many bits to send for this scan for each tile. A number of options are available and require that when the server decides to send a given number of bits from a given tile string, the client/receiver can decide to receive the same number of
10 bits and put them in the same tile.

For most purposes it is sufficiently general for the priority index for each tile to have the form of an unsigned integer with a sufficient number of bits to allow adequately fine increments of priority. The
15 simplest arrangement is thus to use an integer in some range such as 0 32 as the tile priority and send a number of bits from the tile stream which equals the priority index.

FIG 4 illustrates the bitstrings formed by the
20 embedded coding of each spatial tile.

Such an approach has a number of advantages. Firstly the length of the string associated with each tile is related to the amount of information on the tile such that the longer the string the more information and
25 vice versa. With a simple priority coding scheme, a situation can arise where two tiles of quite differing complexity are given the same priority and their bits will be transmitted in such a way that the less significant bits from the tile with the shorter bit
30 string will be sent before more significant bits from the tile with the longer bitstring. This situation can be partially corrected by weighting the spatial priorities by the length of each bitstring. The weighting need not be exact and can be compressed thereby ensuring that full
35 transmission of the image finds each tile completing at approximately the same time.

With many images however, the density of information for each tile will vary from bitplane to bitplane - with

some tiles having no information in the upper bitplanes but a lot of low amplitude information, thereby producing a lot of bits for the final bitplanes. For the zero tree codings most tiles eventually have all their bits as refinement bits and the number of bits per tile will be the same for each tile in the lower bitplanes. This means that the bitplanes will not remain in step even with this weighting.

It is advantageous for the decoder to know when a bitplane is complete. If the unit of information transmitted from the server is a single tile bitplane, then equal spatial priority from all tiles will ensure that the bitplanes from all tiles will be delivered in step. This has the disadvantage that the embedding within the bitplane for each tile is no longer relevant. This also means that the priority of each bitplane can be adjusted as part of the process. It is possible to breakdown each tile bitplane into smaller units however this complicates implementation and can lead to greater memory requirements in server and client.

The subdivision of the bitstring for the tile into sequential substrings corresponding to individual tile bitplanes (or smaller units) offers the possibility of finer control over the prioritisation as a function of bitplane depth while maintaining the strict ordering of the bitplanes within the tile.

It is also possible to depart from a simple integer scheme as described above for prioritising the transmission. However it is desirable to send no more than one bitplane from each tile to avoid sending less significant bits before more significant bits and thereby further eroding the embedded character of the transmission. Prioritisation must then be achieved by having a probability of less than 1 of sending the bitplane.

It is possible to achieve this with a pseudo random number generator at each end of the transmission with the same seed so that they produce the same set of random

probability which can then be weighted to make the decisions. This however can produce variable behaviour.

In the present invention the preferred approach is deterministic. As illustrated in FIG 5 which illustrates
5 the priority variables from a series of scans of one tile, this is achieved by assigning another unsigned integer value to each tile which integer value is termed the priority accumulator.

The tiles are scanned in a preset order and at each
10 pass the priority accumulator of each tile is incremented by the priority index. If the priority accumulator plus the priority index is greater than the priority limit, than an overflow of the accumulator will result.

The server then sends the next chunk of data and the
15 accumulator loses the overflow bit. Careful choice of the range of the priority counter and the size of the priority index result in regular updates for each tile with a controlled probability.

A sequence of scans on a single tile is illustrated
20 in FIG 5. At the end of each scan pass, the client/receiver and server communicate any changes in the priority step of the tiles. The priority accumulator is not modified. If the priority is a simple function of the location of the tile then this does not involve a
25 large amount of data being communicated, thereby allowing the client/receiver to interactively control the transmission when a duplex line is available.

In use the method in accordance with the present invention can have numerous applications. For example a
30 user with a low band-width access to the InterNet such as a satellite or digital mobile (GSM) connection ion the field may need to view images available on the web. The user dials in and runs Netscape, connects to the homepage holding the images which could be an image database and
35 clicks on to view some images. The user may looking for images with certain characteristics but is unaware in advance which images are suitable, but will recognise them as such when seen.

Standard image transfer within Netscape can be very slow via modem. However when transmitted in accordance with the present invention, a fuzzy version of the image quickly appears on the user's screen and quite soon it is possible to recognise the basic features of the image. If one of these is of interest, the user clicks on to the portion of interest. The image continues to be downloaded but the image gets rapidly clearer in the nominated area and remains fuzzy elsewhere. After only a fraction of the image has been transmitted, the user may have seen all that is necessary and a decision can be made as to whether the image is required.

It will be appreciated that the system and method in accordance with the present invention have a number of advantages over known progressive image transmission systems and methods. These include:-

- . An ability for a user to interactively prioritise regions of the image being transmitted.
- . A user can select a point or region in the image and have the server send data preferentially from that region.
- . The ability to provide interactive prioritisation while retaining the embedded nature of the underlying image representation and without significant compromising of compression.
- . The present invention allows an arbitrary image to be transmitted across a network such that at any point in the transmission the client/user/receiver requesting the image can prioritise regions of the image so that the information transmitted will preferentially enhance the image in a manner which varies across the image smoothly.
- . After transmission of as little as 1-2% of an image, the user has enough information to identify regions of potential interest. The user can then click on that area and define a smooth priority map which can be communicated to the server such that the image will appear to resolve smoothly and

progressively around the selected region.

. The user can redefine the priority without the server having to reformat the image representation at the transmission end and without having to resend
5 any information.

It will of course be realised that whilst the above has been given by way of an illustrative example of this invention, all such and other modifications and variations hereto, as would be apparent to persons
10 skilled in the art, are deemed to fall within the broad scope and ambit of this invention as is herein set forth.

Claims

1. A method of progressively transmitting an image in which image compression techniques rely on spatial tiling
5 of the image, said method including:-

allocating variable priority values to spatial regions within said image whereby a receiver of a transmitted image can interactively define the spatial focus of the image during transmission thereof.

10

2. A method as claimed in claim 1, wherein variable priority values are allocated to independent spatially localised tiles within said image by encoding an embedded representation such that truncations of said
15 representations for each tile can be used to generate valid approximations to said tiles.

3. A method as claimed in claim 2, wherein said compression techniques are based on embedded zerotree
20 coding systems.

4. A method as claimed in claim 2, and further including:-
separating the bitstreams associated with each tile
25 and weighting each bit.

5. A method as claimed in claim 4, and further including:-
establishing an algorithm at each end of the
30 transmission to determine the ordering of the information from the tiles.

6. A method as claimed in claim 4, wherein said bits are weighted by assigning a priority index for each tile,
35 said priority index comprising a first unsigned integer having a sufficient number of bits to facilitate fine increments of priority.

7. A method as claimed in claim 6, wherein said priority index for each is an integer within a predetermined range; said method further including:-

5 transmitting a number of bits from the tile stream which equals the priority index.

8. A method as claimed in claim 4, wherein the bits in the bitstring representation of each tile are weighted in accordance with the length of each bitstring.

10

9. A method as claimed in claim 6, and further including:-

15 assigning a priority accumulator to each tile, said priority accumulator comprising a second unsigned integer value.

10. A method as claimed in claim 9, and further including:-

20 scanning said tiles in a preset order and at each pass thereof incrementing said priority accumulator of each tile by said priority index.

11. A method as claimed in claim 10, and further including:-

25 transmitting a quantity of information each time the accumulator overflows.

12. An image transmissiom system for progressively transmitting an image in which image compression techniques rely on spatial tiling of the image, said system including:-

30 prioritising means for allocating variable priority values to spatial regions within said image whereby a receiver of a transmitted image can interactively define the spatial focus of the image during transmission thereof.

35

13. A system as claimed in claim 12, and further

including:-

separating means for separating the bitstreams associated with each tile, and

weighting means for weighting each bit.

5

14. A system as claimed in claim 13, and further including:-

means for establishing an algorithm at each end of the transmission to determine the ordering of the information from the tiles.

10

15. A system as claimed in claim 14, and further including:-

15 assigning means for assigning a priority accumulator to each tile, said priority accumulator comprising a second unsigned integer value,

scanning means for scanning said tiles in a preset order and at each pass thereof incrementing said priority accumulator of each tile by said priority index, and

20

transmitting means for transmitting a quantity of information each time the accumulator overflows.




Figure 1.




Figure 2.




Figure 3.




Figure 4.




Figure 5.

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/AU 97/00724

A. CLASSIFICATION OF SUBJECT MATTER		
Int Cl ⁶ : G06T 9/40; H04N 1/64		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) IPC ⁶ : As above (plus G06F and H03M)		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched AU: IPC as above		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) WPAT, INSPEC (image, transmi., COD:, progressive)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	WO 97/33425 (TELEFON.L M ERICSSON) 12 September 1997, pages 1-7	1, 12
Y	US 5315670 (SHAPIRO) 24 May 1994 column 12	1, 12
Y	"A New, Fast and Efficient Image Codec Based on Set Partitioning in Hierarchical Trees" (Said and Pearlman) IEEE Transactions on Circuits and Systems for Video Technology Volume 6, No. 3, June 1996 pages 243-250 especially page 243	1, 12
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex		
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>		
Date of the actual completion of the international search 19 December 1997		Date of mailing of the international search report 13 JAN 1998
Name and mailing address of the ISA/AU AUSTRALIAN INDUSTRIAL PROPERTY ORGANISATION PO BOX 200 WODEN ACT 2606 AUSTRALIA Facsimile No.: (02) 6285 3929		Authorized officer DALE SIVER Telephone No.: (02) 6283 2196

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/AU 97/00724

C (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5122875 (RAYCHAUDHURI et al) 16 June 1992 Abstract	1, 12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No.
PCT/AU 97/00724

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
WO	97/33425	AU	19500/97	SE	9600853	SE	9603979
US	5315670	JP	7501664	WO	9310634		
US	5122875	AT	149772	AU	13309/92	BR	9205675
		CN	1065567	CZ	9301730	CZ	9600028
		DE	69217921	EP	573517	FI	933759
		HU	9302256	HU	65292	JP	6505378
		MX	9200829	PT	100169	SK	924/93
		SK	673/96	TR	26452	WO	92/16071

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.